

# Eiffel Inspire 7000 4T SG/CD (JASO MA2) series

Monograde 4 Stroke Motor Oil



## Product Data Sheet

---

### Product Description

Eiffel Inspire 7000 4T SG/CD JASO MA2 series is designed with high quality base stocks and advanced technology additive system to provide high level of protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise. This product meets the requirements of most motorcycle manufacturers and is suitable for use in 4 stroke gasoline engines, naturally aspirated or turbo charged engines, operating in all round seasons and adapted to vehicles equipped with catalytic converters running on unleaded fuels.

### Features & Benefits

- Superior protection against viscosity and thermal breakdown.
- Excellent detergency and dispersancy.
- Superior sludge protection for greater engine reliability.
- Enhanced wear protection and improved engine cleanliness.
- Easier cold starts and improved fuel economy compared to mono-grade engine oils.

### Specifications

**Eiffel Inspire 7000 4T series meets or exceeds following International and Builder specification:**

- API SG, CD
- JASO MA2
- JASO 4T Clutch performance

### Application

Eiffel Inspire 7000 4T is suitable for use in following:

- Motorcycle 4 Stroke gasoline engines.
- Naturally aspirated or turbo-charged engines.

### Typical Characteristics

Eiffel Inspire 7000 4T	Test Method	Units	40	50
Density @ 15 °C	ASTM D 4052	gm/cc	0.900	0.904
Viscosity @ 100 °C	ASTM D 445	cSt	15.4	20.2
Viscosity @ 40 °C	ASTM D 445	cSt	158	234
Viscosity Index	ASTM D 2270	-	99	99
Pour Point	ASTM D 97	°C	-18	-18
Flash Point (COC)	ASTM D 92	°C	236	242
Total Base Number	ASTM D 2896	mg KOH/g	5.5	5.5
Phosphorous	ASTM D 4951	% wt	0.082	0.082

*The above figures are typical of blends with normal production tolerance and do not constitute a specification.*