

Eiffel Presti Silver SL series

Multigrade Gasoline and Diesel Engine Oil



Product Data Sheet

Product Description

Eiffel Presti Silver SL series is designed with high quality semi-synthetic base stocks and advanced technology additive system to provide very high level of engine protection and performance. It is suitable for higher mileage gasoline fueled automobiles and light duty trucks requiring an API SL specification, where very high viscosity index oils are preferred to provide longer oil drain intervals in modern engines and better oil consumption control in older vehicles where oil usage (burning) is an issue.

Features & Benefits

- Superior protection against viscosity and thermal breakdown.
- Excellent detergency and dispersancy.
- Superior sludge protection for greater engine reliability.
- Enhanced wear protection and improved engine cleanliness.

Specifications

Eiffel Presti Silver meets or exceeds following International and Builder specifications:

- API SL, SJ, CF
- ACEA A3/B4
- MB Approval 229.1
- VW 505 00

Application

Eiffel Presti Silver is suitable for use in following:

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Naturally aspirated or turbo-charged engines.
- Fuel injected or indirect injection diesel engines fitted with blow-by recirculation systems.

Typical Characteristics

Eiffel Presti Silver	Test Method	Units	10W-30	10W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.868	0.870
Viscosity @ 100 °C	ASTM D 445	cSt	10.4	14.30
Viscosity @ 40 °C	ASTM D 445	cSt	62.6	95
Viscosity Index	ASTM D 2270	-	156	155
Pour Point	ASTM D 97	°C	-36	-36
Flash Point (COC)	ASTM D 92	°C	215	230
Total Base Number	ASTM D 2896	mg KOH/g	8.0	8.0
Phosphorous	ASTM D 4951	% wt	0.098	0.098
CCS Viscosity	ASTM D 5293	cP	5550 @ -25 °C	5650 @ -25 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.