

# EIFFEL NOBLE ULTIMATE SN SERIES

Multigrade Gasoline and Diesel Engine Oil



## Product Data Sheet

**Product Description** -Eiffel Noble Ultimate SN series are formulated with high quality base stocks and balanced additive system to provide high level of engine protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise. This product meets the requirements of most car manufacturers and is suitable for standard services. This is a very high-quality mineral oil with proven performance. It has been upgraded to meet and exceed ACEA A3/B4. It is suitable for most 4-stroke gasoline and diesel cars as well as light trucks.

## Features & Benefits

- Good engine cleanliness, due to improved detergency and dispersancy.
- Good wear protection and improved resistance to oxidation.
- Superior protection against viscosity and thermal breakdown.
- Superior sludge protection for greater engine reliability.
- Easier cold starting compared to mono-grade engine oils.

## Specifications

**Eiffel Noble Deluxe meets or exceeds following International and Builder specifications:**

ACEA	A3/B3	MB 229.1
ACEA	A3/B4	PSA B71 2295
API	SN/CF	VW 501.01
FIAT	9.55535-D2	VW 505.00
FIAT	9.55535-G2	

## Application

Eiffel Noble Ultimate is suitable for use in following:

4-stroke gasoline passenger cars engines (multi-valve, turbo, etc.); 4-stroke diesel engines, with or without turbo. High compatibility with biodiesel, based on extensive field trials.

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Pleasure boats, motorcycles without wet clutch, etc.
- Moderate duty LPG vehicles.
- Naturally aspirated or turbo-charged indirect injection diesel engines.

## Typical Characteristics

Eiffel Noble Ultimate	Test Method	Units	15W-40	15W-50
Density @ 15 °C	ASTM D 4052	gm/cc	0.875	0.875
Viscosity @ 100 °C	ASTM D 445	cSt	14.5	18.9
Viscosity @ 40 °C	ASTM D 445	cSt	109	145.9
Viscosity Index	ASTM D 2270	-	145	147
Pour Point	ASTM D 97	°C	-30	-30
Flash Point (COC)	ASTM D 92	°C	230	230
Total Base Number	ASTM D 2896	mg KOH/g	8.2	8.2
CCS Viscosity	ASTM D 5293	cP	5310 @ -20 °C	5810 @ -20 °C

*The above figures are typical of blends with normal production tolerance and do not constitute a specification.*

---

For further information, please contact: [sales@eiffellubricants.com](mailto:sales@eiffellubricants.com)