

Eiffel Noble Premium SF/CD

Multigrade Gasoline and Diesel Engine Oil



Product Data Sheet

Product Description

Eiffel Noble Premium SF/CD series are formulated with premium quality base stocks and balanced additive system to provide superior level of engine protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise. This product meets the requirements of most old and newer model cars and is suitable for standard services.

Features & Benefits

- Premium protection against viscosity and thermal breakdown.
- Good engine cleanliness, due to improved detergency and dispersancy.
- Premium sludge protection for greater engine reliability.
- Good wear protection and improved resistance to oxidation.
- Excellent cold starting compared to mono-grade engine oils.

Specifications

Eiffel Noble Premium meets or exceeds following International and Builder specifications:

- API SF, CC, CD
- ACEA A2/B2

Application

Eiffel Noble Premium is suitable for use in following:

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Naturally aspirated or turbo-charged indirect injection diesel engines.

Typical Characteristics

Eiffel Noble Premium	Test Method	Units	15W-40	15W-50
Density @ 15 °C	ASTM D 4052	gm/cc	0.875	0.879
Viscosity @ 100 °C	ASTM D 445	cSt	14.60	19.66
Viscosity @ 40 °C	ASTM D 445	cSt	104	154.6
Viscosity Index	ASTM D 2270	-	145	147
Pour Point	ASTM D 97	°C	-30	-30
Flash Point (COC)	ASTM D 92	°C	230	236
Total Base Number	ASTM D 2896	mg KOH/g	5.8	5.8
Phosphorous	ASTM D 4951	% wt	0.078	0.078
CCS Viscosity	ASTM D 5293	cP	6020 @ -20 °C	6060 @ -20 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.