

# Eiffel Vista Silver 15W-30 CF

High Performance Multigrade Diesel Engine Oil



## Product Data Sheet

---

### Product Description & Application

Eiffel Vista Silver 15W-30 CF diesel engine oil is formulated with high quality base stocks and selected additives to ensure optimum performance and protection for diesel engines requiring an API CF-4 specification. Suitable for diesel engines for both turbocharged and normally aspirated engines operating under severe service conditions in all seasons.

### Features & Benefits

- Good oxidation & thermal stability reduces sludge build up and keeps the engine cleaner.
- Optimum wear protection to extend engine efficiency and service life.
- Improved fuel economy, due to high fluidity at low temperatures.
- Reduced oil consumption at high operating engine temperatures.
- Improved resistance to deposit formation keeps engine clean to give your vehicle maximum power under extreme operating conditions.
- Optimum TBN reserves provide improved acid neutralization and corrosion protection, especially in old heavy duty diesel engines.

### Specifications

Eiffel Vista Silver 15W-30 meets or exceeds following International and Builder specifications:

- API CF, SJ
- ACEA E2
- MTU OIL Category-1
- MAN 270/271
- VOLVO VDS
- Deutz DQC -I-05
- MB 228.0/1

### Typical Characteristics

Eiffel Vista Silver	Test Method	Units	15W-30
Density @ 15 °C	ASTM D 4052	gm/cc	0.884
Viscosity @ 100 °C	ASTM D 445	cSt	11.5
Viscosity @ 40 °C	ASTM D 445	cSt	81.7
Viscosity Index	ASTM D 2270	-	142
Pour Point	ASTM D 97	°C	-27
Flash Point (COC)	ASTM D 92	°C	220
Total Base Number	ASTM D 2896	mg KOH/g	9.01
CCS Viscosity	ASTM D 5293	cP	5100 @ -20 °C

*The above figures are typical of blends with normal production tolerance and do not constitute a specification.*