

Eiffel Fabela Xtreme HD 5W-30 CK-4

Fully Synthetic-High Performance Multigrade Diesel Engine Oil



Product Data Sheet

Product Description & Application

Eiffel Fabela Xtreme HD 5W-30 CK-4 is an advanced performance low-SAPS fully synthetic diesel engine oil formulated with severely refined base stocks and sophisticated technology additives to provide outstanding engine performance in the latest emission designs, including those with after treatment systems with Diesel Particulate Filters (DPF), Selective Catalytic Reduction (SCR) and Diesel Oxidation Catalyst (DOC). It may be used in both new and old diesel engines for On & Off highway applications, due to its backward compatibility down to CJ-4 specifications and may also be used in gasoline engines requiring the API SN specification. They are specifically formulated to deliver excellent wear and engine protection, extended drain capability with excellent TBN retention, outstanding high temperature performance and engine cleanliness.

Features & Benefits

- Excellent oil consumption control, due to very oil low volatility and less oil top-up during operation.
- Outstanding oxidation & thermal stability reduces sludge deposits and keeps the engine cleaner.
- Excellent engine protection by providing outstanding protection against corrosive & abrasive wear.
- Improved shear stability maintains viscosity in-grade under severe, high temperature service conditions.
- Excellent low temperature pumpability ensures smooth cold starting and improved fuel economy.
- Excellent TBN reserves provide improved acid neutralization and corrosion protection, which helps in extending oil drain interval in both new & old engines using either low (500 ppm) or ultra-low (15 ppm) sulfur diesel fuel.

Specifications

Eiffel Fabela Xtreme HD meets or exceeds following International and Builder specifications:

- API CK-4, CJ-4, CI-4 Plus, CI-4, CH-4
- ACEA E8/E11/E7-22, E6/E9-16
- Scania LDF-4
- MACK EOS-4.5
- Detroit Diesel Power Guard 93K222
- CUMMINS CES 20086
- MTU 3.1
- CAT ECF-3
- MB 228.51 (DTFR 15C110)
- VOLVO VDS-4.5
- MAN M 3775/M 3677
- Renault VI RLD-3
- Duetz DQC IV-18 LA
- JASO DH-2

Typical Characteristics

Eiffel Fabela Xtreme HD	Test Method	Units	5W-30
Density @ 15 °C	ASTM D 4052	gm/cc	0.848
Viscosity @ 100 °C	ASTM D 445	cSt	10.4
Viscosity @ 40 °C	ASTM D 445	cSt	58.65
Viscosity Index	ASTM D 2270	-	169
Pour Point	ASTM D 97	°C	-42
Flash Point (COC)	ASTM D 92	°C	220
Total Base Number	ASTM D 2896	mg KOH/g	10.0
Sulfated Ash	ASTM D 874	% wt	1.0
CCS Viscosity	ASTM D 5293	cP	4560 @ -30 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.