

Eiffel Presti Supreme 4AT 10W-40 SP/JASO MB

Synthetic Blend – Extra High-Performance Scooter Oil



Product Data Sheet

Product Description

Eiffel Presti Supreme 4AT 10W-40 SP is designed with high quality synthetic blend base stocks and advanced technology additive system to provide high level of protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise. This product meets the requirements of most scooter manufacturers, with naturally aspirated or turbo charged engines, operating in all round seasons and adapted to vehicles equipped with catalytic converters running on unleaded fuels. It is suitable for modern 4-stroke Scooters of European, Taiwanese, Japanese, Chinese, Indian manufacturers.

Features & Benefits

- Superior protection against viscosity and thermal breakdown.
- Excellent detergency and dispersancy.
- Superior sludge protection for greater engine reliability.
- Enhanced wear protection and improved engine cleanliness.

Specifications

Meets or exceeds following International and Builder specifications:

- API SP, SN Plus, SN, SL, SJ
- ACEA A3/B3
- JASO MB

Application

Eiffel Presti Supreme 4AT is suitable for use in following:

- Modern 4-stroke Scooter engines, wherein potential damage due to pre-ignitions has to be avoided.
- Naturally aspirated, turbo-charged, gasoline direct injection (GDI) or turbo-charged gasoline direct injection (TGDI) engines.

Typical Characteristics

Eiffel Presti Supreme 4AT	Test Method	Units	10W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.868
Viscosity @ 100 °C	ASTM D 445	cSt	15.85
Viscosity @ 40 °C	ASTM D 445	cSt	109.85
Viscosity Index	ASTM D 2270	-	154
Pour Point	ASTM D 97	°C	-33
Flash Point (COC)	ASTM D 92	°C	230
Total Base Number	ASTM D 2896	mg KOH/g	7.0
CCS Viscosity	ASTM D 5293	cP	5250 @ -25 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.